

Specifications subject to change

speco technologies"

Color Facial Identification Camera with 24V AC Line Locked Operation and 2.6-6mm Varifocal Lens



Sits on a counter or table

TC-25VF

Features:

The TC-25VF allows you to view a person's face by placing an unobtrusive camera at eye level. Pictures of the top of your customer's head or hat are a thing of the past.

Our TC-25VF counter camera operates on 24 Volts AC power which allows for line lock and "drift free" color pictures. It offers double speed WDR technology and a 2.6 to 6mm auto iris Varifocal lens.

The base allows for easy horizontal angle adjustment and the camera location inside the housing is vertically adjustable. The cable can be routed through the bottom of the base or the rear for a more concealed and secure installation.

Specifications.

- Removable top mounted IR LEDs illuminate a person's face and balances backlit scenes
- · Camera is height adjustable within the tower
- The camera can be tilted within the housing to achieve all required angles
- The tower is horizontally adjustable and locks into position using set screws
- 2.6 to 6mm auto iris Vari-focal lens allows you to "fine tune" your coverage
- Ultra high 480 lines of resolution
- 1/3" color Sony double speed CCD sensor
- · Day/Night operation with a mechanical IR cut filter
- Sensitivity to 0 lux within a 10 foot range, 0.03 lux beyond 10 feet
- WDR (Wide Dynamic Range) technology minimizes back-lighting problems
 - Cable can be routed through the bottom or rear of the tower
 - Standard tower height is 24". Customized heights are available
 - · Customize the look of your tower with a paint color or "slide-in" advertising panels
 - 24 volt AC operation with line-lock and adjustable v-phase
 - Power requirements: 24V AC @ 40VA

Package Includes:

Tower Camera Instruction Manual Warranty Attachable IR LED Array

For more information contact us at:

Speco Technologies 200 New Highway, Amityville, NY 11701 Web: www.specotech.com Toll Free: 1-800-645-5516 In Metro NY: 631-957-8700 Fax: 631-957-9142 or 631-957-3880